





















DNG-50 LOW FOG





Information

Product Description

Scan QR Code For Detail

The DNG-50 delivers smooth, ground-hugging fog using advanced ultrasonic technology—no dry ice or liquid CO2 required. Designed for small to medium-sized venues, it produces clean, consistent low fog ideal for weddings, theaters, studios, and special events. Compact, quiet, and energy-efficient. Its perfect mix ratio keeps the fog close to the ground, creating immersive atmospheres with ease. Whether for permanent installs or mobile setups, the DNG-50 provides professional-grade fog effects with exceptional reliability and

Feature

visual impact.

- No Dry Ice or Liquid CO2 Required
- Continuous Low Fog Output
- Voltage Protection
- Low Water Level Sensor
- Optional Wireless / W-DMX Control Module



Rated Power



Dimension



Weight

1200W



865 mm (L) 34.06 inch 355 mm | W | 13.98 inch 517 mm (H) 20.36 inch

25.4 kg 56.00 lbs



Technical Specification



Fluid Consumption

16 ml/min (100% Output)



Fluid Tank Capacity

2.5 Liter 0.66 Gallon









Interface



XLR 3-Pin & 5-Pin Connector (DMX)



SEETRONIC Connector (Power)

Control Methods













Note





















